

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification⁵:

H04H 1/00

A1

(11) International Publication Number:

WO 94/22243

(43) International Publication Date: 29 September 1994 (29.09.94)

(21) International Application Number: PCT/US94/02365


(22) International Filing Date: 4 March 1994 (04.03.94)

(30) Priority Data:
08/031,763 15 March 1993 (15.03.93) US(71) Applicant: MACROVISION CORPORATION [US/US]; 700
El Camino Real East, Mountain View, CA 94040 (US).(72) Inventor: RYAN, John, O.; 22015 Creekside Court, Cupertino,
CA 95014 (US).(74) Agent: BRILL, Gerow, D.; Macrovision Corporation, 700 El
Camino Real East, Mountain View, CA 94040 (US).(81) Designated States: AT, AU, BB, BG, BR, CA, CH, CN, DE,
DK, ES, FI, GB, HU, JP, KP, KR, LK, LU, MG, MN, MW,
NL, NO, NZ, PL, RO, RU, SD, SE, VN, European patent
(AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC,
NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA,
GN, ML, MR, NE, SN, TD, TG).

Published

With international search report.

(54) Title: RADIO RECEIVER FOR INFORMATION DISSEMINATION USING SUBCARRIER



(57) Abstract

A radio receiver receives FM subcarrier transmissions, and stores the transmitted textual information in a random access memory. The information is typically news, weather, sports, entertainment or other information of interest. A user interface allows selection from the memory of the stored information via a set of menus controlling a hierarchical database, so as to access particular items of information. A speech synthesizer accepts the accessed textual information items and transforms them into spoken speech. The user interface is either by voice or a single or multi-position switch allowing scanning through and selection from the menu items.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

RADIO RECEIVER FOR INFORMATION
DISSEMINATION USING SUBCARRIER

BACKGROUND OF THE INVENTION

5 Field of the Invention

This invention relates to a radio broadcasting system for transmission of alphanumeric information to a specially adapted receiver.

DESCRIPTION OF THE PRIOR ART

10 Numerous systems transmit information on FM radio subcarriers. See for instance, U.S. Patent 5,152,011 issued to Schwob, September 29, 1992. Also known is a single sideband communication system with FM data capability for transmission of analog voice signals. See
15 U.S. Patent 4,852,086 issued to Eastmond et al., July 20, 1989.

Also known is FM radio sideband broadcasting to specially adapted computers for transmission for instance of news and financial information. Commercially available
20 products available from Mainstream, Telemet, and DeskTop Data broadcast data over FM radio sidebands for receipt by personal computers equipped with special FM radio receivers and software. Typically information is transmitted in digital form, received, and stored in the
25 computer memory for access by the computer user using menu driven software. The data is displayed on the computer screen in conventional alphanumeric form. One product in this category is News Edge, a news service available from DeskTop Data, Inc. of Waltham, Massachusetts which
30 delivers a number of news and financial information services to a user via FM radio sideband. Software provided with the product scans incoming information and when the incoming information meets parameters set by the

user, the information is saved to disk and/or displayed on the computer screen.

These systems have the disadvantage of requiring a personal computer as a platform, and providing information only on a computer screen. The usual computer skills are needed in order to operate such systems, which tend to be quite expensive.

SUMMARY OF THE INVENTION

A system for receiving information via radio sidebands (subcarriers) includes an FM subcarrier tuner which extracts encrypted data from a radio transmission. Conditional access circuitry decrypts the data which is stored in a random access memory. A user interface (either a simple manual or voice control) driving a hierarchy of menus allows a user to access the information by indicating his selections from the menus; the system then extracts the information from the database in decrypted text form. A speech synthesizer converts the text information to an audio signal for provision to the user via a loud speaker or earphones.

This system may be standalone or a part of an existing radio receiver, sharing components of the radio receiver. One embodiment of the user control is a four way switch (the positions corresponding for instance to the cursor control keys on a computer) for selection from and scanning through the menus. Typically the system includes approximately four megabits of memory, sufficient to store information for 10 hours of audio. The information is for example news, sports, weather, cultural information, advertisements, or commercial listings. The information is transmitted in digital form as (encrypted) ASCII text which is readily stored and voice synthesized.

Other features are user control over the speed at which the synthesized speech is output, and a channel

skipping tuner for finding the particular FM radio station subcarrier on which the service is provided. An optional printer produces hard copy output, and the speech synthesizer may under either automatic or user control produce different types of voices. Also, the user has the opportunity to preselect database items, thereby to construct a personal profile so as to extract particular information without having to scan through all the menus.

BRIEF DESCRIPTION OF THE DRAWING

10 Figure 1 shows a block diagram of an apparatus in accordance with the present invention.

DETAILED DESCRIPTION OF THE INVENTION

Figure 1 shows a device in accordance with one embodiment of the invention. Conventional FM radio antenna 10 (as used for instance in automobile or portable radios) provides a received radio signal to FM subcarrier tuner 12 of the type well known in the art for extracting an FM subcarrier signal. As is well known, these subcarrier signals are typically transmissions of digitized data on subcarriers leased from commercial FM radio stations. FM subcarrier tuner 12 provides on line 14 the extracted data (which typically is encrypted) to conditional access circuitry 16.

Conditional access circuitry 16 ensures that the data is decrypted only if the proper key or command has been provided, as described below. Conditional access circuitry 16 decrypts the received data (as authorized by microcontroller 20 over lines 22) and in one embodiment provides plain ASCII text (or other alphanumeric text) on line 26 for storage to conventional integrated circuit random access memory (RAM) 28. In one embodiment RAM 28 includes approximately 4 megabits of storage capacity. This information is accessed under control of microcontroller (microprocessor) 20 via control signals at

- 4 -

lines 24, to determine which particular items of data stored in RAM 28 are to be provided via output line 32 to speech synthesizer 30.

In other embodiments, the received data is stored as encrypted data or in another convenient form and converted to a form usable by the speech synthesizer prior to being converted to speech. In this case, each data item would be "tagged" with an unencrypted designation to allow retrieval of the stored encrypted data from the database.

10 Speech synthesizer 30 is of the type commercially available for example from Berkeley Speech Technologies, Berkeley, California. This system converts ASCII text into understandable and well modulated audio analog signals. The audio analog signals are provided on line 34
15 to a conventional audio amplifier 36 and hence to a loud speaker or earphones 38 to be listened to by the user.

User interface 40 inputs commands on line 42 to microcontroller 20 to determine which items of data from random access memory 28 are to be listened to.

20 The transmitted information is categorized, stored, and accessed in a conventional hierarchical database in RAM 28 under control of microcontroller 20.

In one embodiment user interface 40 is a voice activated command system. For instance the device is
25 turned on and initialized by the user's spoken "ON" command. It then responds by vocally announcing via loud speaker 38 the major database categories available e.g. "NEWS", "SPORTS", "ENTERTAINMENT", etc. When the desired category has been announced the user responds by saying
30 "YES". The device then announces again the sub-categories of the selected major category, and the user again selects the desired sub-category with a spoken "YES" until the specific item needed is accessed. For example, the category and sub-category path to the latest news
35 regarding the General Motors Corporation might be "NEWS ... BUSINESS .. NATIONAL .. AUTOMOTIVE .. GM." The path

to a review of the recent movie Aladdin might be
"ENTERTAINMENT .. HOLLYWOOD .. MOVIE REVIEWS .. ALADDIN."
Typically items will be reached after four or five "YES"
responses from the user. In one embodiment three
5 additional spoken commands by the user such as "BACK"
"STOP" and "GO" are sufficient to provide the user
effective and rapid control of the system.

In another embodiment a switch assembly having for
instance four positions (up, down, left, right)
10 corresponding to the familiar cursor control on a
computer, with each position indicating one of four
commands, is provided for user manual operation. This
switch may be adapted to attach to the steering wheel of
an automobile, for use by the driver. The control is
15 linked to the rest of the device by wire, infrared, or
ultrasonically, as is a conventional television remote
control.

Another version uses a one-position control switch.
The user briefly depresses the switch to select the
20 category or item as announced or to scan through the
menus. Briefly depressing the switch while an actual data
item is being read executes "stop." Depressing it again
then executes "go." Holding the switch down for a second
or two executes "back" at any time, to return to a
25 predetermined point in the database.

The FM subcarrier tuner 12, microcontroller 20,
conditional access circuitry 16 and random access memory
28 typically remain powered at all times (by battery power
if necessary) to receive a continuous update of the
30 broadcast database, and thereby to store current news in
RAM 28.

In one version the device of Figure 1 is a portable
unit (similar to a portable radio) and includes the user
voice or manual interface. In another embodiment the
35 device of Figure 1 is build into a conventional portable

- 6 -

radio or automobile radio, sharing where possible common components.

In one embodiment user interface 40 has a speed control to determine the output speed of speech synthesizer 30. Speech synthesizer 30 may receive information on line 32 faster than normal speaking speed. It is well known that people can understand speech at faster than normal speech rates. Thus the user by pushing a button on the receiver unit or providing the proper verbal command increases the speech speed, so as to obtain information faster, analogous to skimming printed material.

In the embodiment using a voice activated user interface 40, the number of commands provided is limited (for instance to 5 to 10) and hence a relatively simple commercially available voice input recognition circuit is sufficient.

In another embodiment, the user interface for an automobile-based system is associated with a heads-up display, expected to be available in various automobiles in the near future. This provides visual display of the database menu items analogous to a computer screen, to allow faster access to the database menus.

Advantageously, by transmitting and storing the data in text or alphanumeric form (even though encrypted), the required bandwidth of the transmission channel is vastly reduced, as are the memory requirements, thereby substantially reducing the component cost. A typical transmission speed is one kilobaud, as is now used in FM subcarrier transmissions of financial and news information. This is sufficient to download in approximately one hour the needed four megabits of data to random access memory 28.

In use, after purchase of the unit the user programs it to the frequencies of the local stations providing the transmissions. There may be multiple such stations in one

- 7 -

area, due to the limited transmission distance of FM radio. A channel skipping feature (as is now available commercially in various radios) in one embodiment included in microcontroller 20 seeks out stations having a particular signature or frequency, to maintain reception even when moving from the transmission area of one station carrying the service to the transmission area of a second station carrying the service. It would take less than a minute for the system to scan the entire FM band looking for the signature transmission.

The data encryption/access is accomplished in several ways. In one embodiment a simple addressed on/off command is transmitted (without data encryption) to disable individual units belonging to people who have not paid the required monthly subscription fee to receive the service.

In a more sophisticated encryption system where it is believed there is a problem of manufacture and sale of unauthorized units, then proper data encryption is used, requiring receipt of a key and decryption of the data with decryption circuitry. Hence unauthorized units without such dedicated decryption circuitry would not be operative at all.

In one embodiment of an encryption system, (analogous to pay-per-view cable TV encryption), decryption keys are delivered by radio transmission. Each individual receiver unit has a unique "hidden" key of for instance 40 to 50 binary digits in read only memory. Each unit also has a "public" nonhidden serial number. All transmitted data is conventionally encrypted using a master key which is changed periodically, both to force users to pay for the service and to enhance security. Each receiver unit must receive a master key to decrypt the data transmission.

The master key is transmitted to each unit as follows:

Periodically, the transmission of the data is interrupted to transmit key information. The key

- 8 -

information is a series of packets, one packet for each individual receiver unit, with each packet including (1) an address field which is the public serial number of a particular unit; followed by (2) a second field which is the current master key encrypted with the unique "hidden key" of the unit having that particular serial number.

The receivers look for these packets (which are denoted by a particular signature or occur at particular times to avoid confusion with the data). When a particular unit receives the packet including its own address (public serial number), it stores and decrypts the subsequent encrypted master key field, thereby obtaining the master key, in order to decrypt subsequent encrypted data.

15 In a second encryption system embodiment, a uniquely encrypted master key for each individual receiver is physically delivered to each user periodically (such as once a month). The key could be entered into each unit by a keypad, or the key could be embodied in an electronically readable card or device inserted into a suitable port in the receiver.

In another embodiment, speech synthesizer 30 is controlled to provide a variety of particular voices. These voices are selected by the user, i.e. to be male/female or other voices, or the system is programmed via microcontroller 20 to select different voices for different types of or categories of information.

The device of Figure 1 as incorporated in a conventional radio uses antenna 10 of the radio. The FM subcarrier tuner 12 is in addition to the conventional radio tuner or could be part of the radio tuner. The other blocks of Figure 1 (with the exception of amplifier 36 and loud speaker 38) are unique to this system and are added components to a conventional radio.

- 9 -

The above description is illustrative and not limiting; further modifications will be apparent to one of ordinary skill in the art.

- 10 -

I claim:

1. A receiver system comprising:
a radio tuner for extracting data from a radio
signal;
5 a memory for storing the extracted data as a
database;
a user interface for providing a set of menus
describing the database, and for accepting selections
from the set of menus;
10 a controller for selecting data from the
database in response to the accepted selections and
providing the selected data in alphanumeric form; and
a speech synthesizer for converting the selected
data from alphanumeric form to an analog signal
15 representing spoken words.
2. The device of Claim 1, wherein the radio tuner
extracts the data from an FM radio station carrier.
3. The device of Claim 1, wherein the memory stores
the entire database.
- 20 4. The device of Claim 1, wherein the extracted
data is encrypted, and further comprising a decryptor for
decrypting the extracted data.
5. The device of Claim 1, wherein the alphanumeric
form is ASCII text.
- 25 6. The device of Claim 1, wherein the user
interface is voice activated.
7. The device of Claim 1, wherein the user
interface includes:
a manual input device adapted to be mountable on
30 an automobile steering wheel; and

- 11 -

a wireless link from the manual input device to the controller.

8. The device of Claim 1, wherein the user interface includes a control for determining a speed at which the speech synthesizer outputs the analog signal.

9. The device of Claim 2, wherein the radio tuner includes means for channel skip tuning to a particular FM radio station sideband.

10. The device of Claim 1, wherein the memory stores at least four megabits of the data.

11. The device of Claim 1, further comprising:
an amplifier connected to the speed synthesizer for amplifying the analog signal; and
means for converting the amplified signal to sound.

12. The device of Claim 4, wherein the decryptor is enabled by a key received by the radio tuner.

13. The device of Claim 4, wherein the decryptor is enabled by a key device operatively connected to the decryptor.

14. The device of Claim 1, further comprising means for connecting the radio tuner to a radio receiver set.

15. The device of Claim 1, further comprising a device for making a printed copy of the selected data.

16. The device of Claim 1, wherein the speech synthesizer includes means for providing a plurality of voices.

- 12 -

17. The device of Claim 16, wherein the means for providing includes voice selection depending on a category of the selected data.

18. The device of Claim 16, wherein the means for 5 providing includes voice selection in response to user control.

19. The device of Claim 1, further comprising means for designating by a user a hierarchy for the database.

20. A method for transmitting data via a radio
10 signal to a receiver, comprising:
 broadcasting the radio signal;
 extracting the data from the radio signal;
 providing a memory;
 storing the extracted data in the memory as a
15 database;
 providing a set of menus describing the
 database;
 selecting items from the set of menus;
 providing portions of the stored data in
20 response to the selected items, the portions being in
 alphanumeric form; and
 converting the provided portions from the
 alphanumeric form to an analog signal representing
 spoken words.




Figure 1

A. CLASSIFICATION OF SUBJECT MATTER
IPC 5 H04H1/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 5 H04H

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	FR,A,2 651 352 (URBA2000) 1 March 1991 see page 1, line 1 - page 4, line 28; figure 1 ---	1,2,20
X	EP,A,0 373 386 (ROBERT BOSCH G.M.B.H.) 20 June 1990 see column 1, line 1 - column 3, line 55; claims 1,2,4,5,19; figure 3 see column 4, line 19 - line 27 ---	1,20
A	---	2,7
A	DE,A,40 24 132 (BLAUPUNKT-WERKE GMBH) 13 February 1992 see column 1, line 1 - line 27 see column 1, line 36 - column 2, line 59; figure 1 ---	4
	--- -/--	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *I* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

I later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

& document member of the same patent family

Date of the actual completion of the international search

15 June 1994

Date of mailing of the international search report

3 0. 06. 94

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+ 31-70) 340-3016

Authorized officer

De Haan, A.J.

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US,A,4 247 908 (LOCKHART, JR. ET AL.) 27 January 1981 see column 3, line 5 - line 48; figure 1 ---	1,5
A	US,A,4 682 368 (TAKAHASHI) 21 July 1987 see column 1, line 1 - line 56; claims 1,3; figure 2 ---	6
A	WO,A,89 01429 (U.S. CHUNG) 23 February 1989 see claim 1; figures 1,2 ---	7
A	US,A,4 473 824 (CLAYTOR) 25 September 1984 see column 2, line 27 - line 54; claims 1-3,10-12,14,20-22; figures 1,4 -----	1,5,15

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
FR-A-2651352	01-03-91	FR-A- 2642875	10-08-90
		CA-A- 2008789	03-08-90
		EP-A- 0384794	29-08-90
		JP-A- 3001299	07-01-91

EP-A-0373386	20-06-90	DE-A- 3842417	21-06-90
		US-A- 5086510	04-02-92
		US-A- 5239700	24-08-93

DE-A-4024132	13-02-92	NONE	

US-A-4247908	27-01-81	CA-A- 1131316	07-09-82

US-A-4682368	21-07-87	JP-A- 60201751	12-10-85

WO-A-8901429	23-02-89	NONE	

US-A-4473824	25-09-84	NONE	
